
RED3050

4A Fast-switching high-voltage NPN Power Transistor

Features

- High Voltage Capability
- Very High Switching Speed
- High Reliability
- High current capability



TO-126 Package

Applications

- LED lighting
- High Frequency SMPS
- Fluorescent Ballasts

Description

These devices are designed for operation in high voltage high speed circuits, where fast switching in inductive circuits is critical. The transistor has been optimized for low fall-times in order to minimize switching losses.




Figure 1: Block diagram

Table 1: Order Codes

Part number	Package	Packaging
RED3050AJ	TO-126	Tube

Table 2: Absolute Maximum Rating

Symbol	Parameter	Value	Unit
V_{CBO}	Collector-Emitter Voltage (V_{BE} = 0)	500	V
V_{CEO}	Collector-Emitter Voltage (I_B = 0)	300	V
V_{EBO}	Emitter-Base Voltage	9	V
I_C	Collector Current	4	A
I_{CM}	Collector Peak Current (t < 5ms)	8	A
P_{TOT}	Total dissipation at Tc=25°C	50	W
T_{stg}	Storage Temperature	-55 - 150	°C
T_J	Max. Operating Junction Temperature	150	°C


Table 3: Electrical Characteristics (T_{case} = 25°C)

Symbol	Parameter	Test Conditions	Min.	Typ.	Max.	Unit
$V_{(BR)CBO}$	Collector-Base Breakdown Voltage	I_C = 0.1mA	500			V
I_{CBO}	Collector – Base Leakage Current	V_{CE} = 500V, I_E = 0			10	uA
$V_{(BR)CEO}$	Collector – Emitter Breakdown Voltage	I_C = 0.1mA	300			V
I_{CEO}	Collector – Emitter Leakage Current	V_{CE} = 300V, I_C = 0			10	uA
$V_{(BR)EBO}$	Emitter – Base Breakdown Voltage	I_E = 0.1mA	9			V
I_{EBO}	Emitter – Base Leakage Current	V_{EB} = 9V, I_C = 0			10	uA
$V_{CE(sat)}$	Collector - Emitter Saturation Voltage	I_C = 5A , I_B = 1A			1	V
$V_{BE(sat)}$	Base - Emitter Saturation Voltage	I_C = 5A , I_B = 1A			1.5	V
h_{FE}	Current Gain	V_{CE} = 5V, I_C = 1A	15		40	
t_s	Storage Time	(UI9600) I_C = 0.5A	1.5		6	μs
f_t	Gain Bandwidth	V_{CE} = 10V, I_C = 0.5A , f = 1MHz	4			MHz

PACKAGE INFORMATION

Package Dimensions

TO-126 package dimensions are shown below. All units are in mm.




Dimensions	Min	Max
A	7.4	7.6
B	4.95	5.05
C	0.85	1.05
D	2	2.2
E	3.7	3.9
F	7	7.2
G	1.25	1.29
H	0.74	0.78
I	10.65	10.85
J	2.4	2.6
K	5.9	6.1
L1	2.236	2.336
L2	2.236	2.336
M	2.55	2.65
N	Ø 3.05	Ø 3.25
0	Ø 3.50	Ø 3.70
P	1.15	1.25
Q	0.39	0.41
R1	Ø 4.90	Ø 5.10
R2	1.15	1.25

Available packages

Package type	Part number	Moisture Sensitivity Level (MSL)	Packaging
TO-126	RED3050AJ	3 (JEDEC J-STD-020)	Tube

Package Marking



TO-126 top-side marking for RED3050

RED3050= Part Number

WXYZ= Lot Code, e.g. AAAA, AAAB

Status

The status of this Datasheet is shown in the footer.

Status	Product Status	Definition
Preview	In development	The Datasheet contains target specifications relating to design and development of the described IC product.
Preliminary	In qualification	The Datasheet contains preliminary specifications relating to functionality and performance of the described IC product.
Production	In production	The Datasheet contains specifications relating to functionality and performance of the described IC product which are supported by testing during development and production.

Contact Details

RediSem Ltd.
218-219 Photonics Centre
No 2 Science Park East Avenue
Hong Kong Science & Technology Park
Shatin, New Territories
Hong Kong

Tel. +852 2607 4141
Fax. +852 2607 4140
Email: info@redisem.com
Web: www.redisem.com

Disclaimer

The product information provided herein is believed to be accurate and is provided on an “as is” basis. RediSem Ltd assumes no responsibility or liability for the direct or indirect consequences of use of the information in respect of any infringement of patents or other rights of third parties. RediSem Ltd does not grant any licence under its patent or intellectual property rights or the rights of other parties. Any application circuits described herein are for illustrative purposes only. Specifications are subject to change without notice. In respect of any application of the product described herein RediSem Ltd expressly disclaims all warranties of any kind, whether express or implied, including, but not limited to, the implied warranties of merchantability, fitness for a particular purpose and non-infringement of third party rights. No advice or information, whether oral or written, obtained from RediSem Ltd shall create any warranty of any kind. RediSem Ltd shall not be liable for any direct, indirect, incidental, special, consequential or exemplary damages, howsoever caused including but not limited to, damages for loss of profits, goodwill, use, data or other intangible losses. The products and circuits described herein are subject to the usage conditions and end application exclusions as outlined in RediSem Ltd Terms and Conditions of Sale. RediSem Ltd reserves the right to change specifications without notice. To obtain the most current product information available visit www.redisem.com or contact us at the address shown above.